

# Briefing Document: Analysis of Sediment Properties and Their Significance in Transport Dynamics

---

## Executive Summary

Sediment properties—primarily grain size, density, sorting, and porosity—are foundational inputs to sediment transport models. These characteristics directly control:

- Settling velocity
- Threshold of motion
- Partitioning between bedload and suspended load

A central theme is the **statistical characterization of grain size distribution**. Because natural sediments commonly follow a log-normal distribution, analysis is best conducted using the logarithmic **phi ( $\phi$ ) scale**, which simplifies statistical treatment.

Key descriptive parameters include:

- Median diameter  $d_{50}$
- Geometric mean diameter  $d_g$
- Sorting parameter  $\sigma_g$

For non-log-normal distributions, calculations are performed in phi-space and then transformed back to millimeter-space.

Density—particularly the submerged relative density  $R$ —is essential in calculating the Shields parameter and settling velocity, demonstrating the interconnectedness of sediment properties in predicting transport behavior.

---

## 1. Foundational Role of Sediment Properties

Sediment properties are not merely descriptive—they directly govern transport dynamics.

Reliable modeling requires accurate characterization of:

- Grain size
  - Density contrast
  - Sorting
  - Porosity
- 

## **Key Controlled Processes**

### **Settling Velocity**

Determined by particle size, shape, and density.

### **Threshold of Motion**

Controlled by grain size and submerged weight.

### **Bedload vs. Suspended Load**

Strongly influenced by grain size and settling velocity.

These properties underpin:

- Shields parameter
  - Transport rate formulas
  - Dimensionless mobility parameters
- 

## **2. Core Physical Properties of Sediments**

---

### **2.1 Composition**

Natural sediments consist of mineral particles and organic matter.

## Common Mineral Constituents

- Quartz
- Feldspar
- Limestone
- Basalt
- Mica
- Heavy minerals (e.g., magnetite, ilmenite)

In most fluvial and coastal sands, **quartz and feldspar dominate** due to weathering resistance.

Mineralogy influences:

- Density
  - Durability
  - Transport behavior
- 

## 2.2 Density

Density controls submerged weight and mobility.

### Definitions

- Sediment density:  $\rho_s$
- Fluid density:  $\rho$

Relative density:

$$s = \frac{\rho_s}{\rho}$$

Submerged relative density:

$$R = s - 1 = \frac{\rho_s - \rho}{\rho}$$

Appears directly in:

- Settling velocity formulas
- Shields parameter

---

## Typical Relative Density Values

| Material    | Relative Density (s) |
|-------------|----------------------|
| Quartz sand | ~2.65                |
| Limestone   | 2.6–2.8              |
| Basalt      | 2.7–2.9              |
| Magnetite   | 3.2–3.5              |

---

## 2.3 Porosity

Porosity describes void fraction:

$$n = \frac{V_{void}}{V_{total}}$$

### Typical Ranges

| Material Type          | Porosity  |
|------------------------|-----------|
| Uniform sands          | 0.30–0.50 |
| Poorly sorted mixtures | < 0.30    |
| Fresh clay             | > 0.8     |

Clay deposits consolidate over time, reducing porosity.

Porosity influences:

- Bulk density
- Permeability
- Bed stability

---

## 2.4 Particle Shape

Natural grains are rarely spherical.

Shape factor:

$$\Psi = \frac{c}{(ab)^{1/2}}$$

where  $a, b, c$  are principal axes.

In practice, shape effects are often absorbed into empirical transport coefficients.

---

## 3. Grain Size Analysis and Distribution

Grain size is the most influential sediment property.

---

### 3.1 Grain Size Definitions

Characteristic diameter:

$d$

Common percentiles:

- $d_{16}$
- $d_{50}$  (median)
- $d_{84}$

Diameter concepts:

- Sieve diameter
- Equivalent sediment diameter

---

## Sediment Size Classes

### Material Diameter (mm) Behavioral Note

|          |             |              |
|----------|-------------|--------------|
| Clay     | < 0.002     | Cohesive     |
| Silt     | 0.002–0.063 | Transitional |
| Sand     | 0.063–2     | Non-cohesive |
| Gravel   | 2–60        | Non-cohesive |
| Cobbles  | 60–200      | —            |
| Boulders | > 200       | —            |

---

## 3.2 The Phi ( $\phi$ ) Scale

Defined as:

$$\phi = -\log_2(d)$$

Inverse:

$$d = 2^{-\phi}$$

Advantages:

- Converts log-normal distribution in mm-space
  - Produces approximately normal distribution in phi-space
  - Enables standard statistical analysis
- 

## 3.3 Grain Size Representation

### Size-Frequency Distribution

- Histogram of grain size classes
- Often approximated by log-normal distribution

## Cumulative Grain Size Curve

- S-shaped curve
  - Used to extract  $d_{16}$ ,  $d_{50}$ ,  $d_{84}$
- 

# 4. Statistical Characterization of Grain Size

---

## 4.1 Log-Normal Distribution Parameters

For log-normal distributions:

### Geometric Mean Diameter

$$d_g = \sqrt{d_{16} \cdot d_{84}}$$

### Sorting (Geometric Standard Deviation)

$$\sigma_g = \sqrt{\frac{d_{84}}{d_{16}}}$$

### Sorting Interpretation

$\sigma_g$  Interpretation  
= 1 Uniform  
< 1.3 Well sorted  
> 1.6 Poorly sorted

---

## 4.2 Advanced Method for Non-Log-Normal Distributions

When distribution deviates from log-normal:

## Step 1: Work in Phi-Space

Compute:

$$\bar{\phi} = \sum(\phi_i^* p_i)$$
$$\sigma_{\bar{\phi}}^2 = \sum((\phi_i^* - \bar{\phi})^2 p_i)$$

where:

- $\phi_i^*$  = class midpoint
- $p_i$  = class fraction

## Step 2: Back-Transform

$$d_g = 2^{-\bar{\phi}}$$
$$\sigma_g = 2^{\sigma_{\bar{\phi}}}$$

These parameters are then used in transport formulas.

---

# 5. Synthesis and Application

Sediment properties are foundational inputs controlling transport systems.

Reliable modeling requires:

- Accurate grain size statistics
- Proper density characterization
- Porosity assessment

The phi-scale transformation is essential for handling log-normal distributions.

Consistent notation ensures compatibility across:

- Shields parameter formulations
- Transport rate equations
- Morphodynamic models